KEG-Ceomat mit Manometer

Druckminderer für 16-g-CO_2-Kapseln



TEILE

1. Spindel
2. Kapselhalter
3. Anschluss

Inbetriebnahme

1. Spindel 1 gegen den Uhrzeigersinn bis zum Anschlag drehen. Das Gewinde der Spindel ist dann vollständig sichtbar, der Ceomat ist geschlossen (0 bar).
2. Kapselhalter 2 abschrauben, eine 16-g-CO_2-Kapsel einlegen und den Kapselhalter fest auf das Gewinde schrauben.
3. Nach einem kurzen Zischen den Kapselhalter von Hand noch etwa eine Vierteldrehung nachziehen. So sitzt die Kapsel sicher in der Dichtung.
4. Ceomat mit dem Anschluss 3 an das gewünschte Gerät anschließen.
5. Spindel 1 im Uhrzeigersinn drehen, bis das Manometer den gewünschten Druck zeigt.

Beim höchsten Druck von ca. 1,3 bar ist ein Klicken zu hören. Voll aufgedreht ist der Ceomat, wenn das Gewinde der Spindel ganz im Gehäuse verschwunden ist.

! Vor dem Einsetzen einer Kapsel muss die Spindel immer ganz zurückgedreht sein (0 bar). Sonst kann der Überdruck das Manometer dauerhaft beschädigen.

Ausführungen

Anschluss 5/8", 3/4" oder 4-mm-Schlauchtülle.

KEG-Ceomat with pressure gauge

Pressure regulator for 16 g CO_2 capsules



PARTS

1. Spindle
2. Capsule holder
3. Connector

Getting started

1. Turn the spindle 1 anticlockwise as far as it will go. The thread of the spindle is then fully visible and the Ceomat is closed (0 bar).
2. Unscrew the capsule holder 2, insert a 16 g CO_2 capsule and screw the capsule holder firmly onto the thread.
3. After a short hiss, tighten the capsule holder by hand by about another quarter turn. This seats the capsule securely in the seal.
4. Connect the Ceomat with its connector 3 to the device.
5. Turn the spindle 1 clockwise until the gauge shows the required pressure.

At the maximum pressure of approx. 1.3 bar you will hear a click. The Ceomat is fully open when the thread of the spindle has disappeared completely into the housing.

! Before inserting a capsule, always turn the spindle back completely (0 bar). Otherwise the excess pressure can permanently damage the gauge.

Versions

5/8" or 3/4" connection, or 4 mm hose nozzle.